



## 20W LED H80 Lamp - 27K/50K

Item # 664/665

L20H80/27K/50K

1 LAMP SPECIFICATION			
1-1	Lamp Type	LED H80	
1-2	Dimmable (Y/N)	NO	
1-3	Base	E26	
1-4	Lamp Finish/Type	H80	
1-5	Lamp Wattage	20W	
1-6	Wattage Comparison (FC on Floor)	200 Incand. (40W CFL)	
1-7	Rated Average Life (hours) L70	50,000	
1-8	LED Type	24 X 0.75W SMD.	
1-9	Reliable Operating Temperature	-4F to 113F	
2 Photometric Characteristics			
2-1	Initial Lumens	1850 (27K) / 2100 (50K)	
2-2	Centre Beam Candle Power (Cd)	TBA	
2-3	Beam Angle (50% I Max) in Degree	140	
2-4	Beam Angle (10% I Max) in Degree	N/A	
2-5	Initial Lumens per Watt	93 (27K) / 105 (50K)	
2-6	Color Temperature	2700K/5000K	
2-7	Color Rendering Index (CRI)	80	
3 Electrical Characteristics			
3-1	Input Line Voltage/Frequency	120V/277V 60 Hz	3-2 Power Factor >0.90
3-3	Lamp rated Wattage	20W	3-4 Input Line Current 170mA(120V) 80mA(277V)
3-5	Total Harmonic Distortion	<30%(120V), <20% +(277V)	3-6 Dimming Range in % Not Dimmable
4 Dimensional Characteristics			
4-1	Nominal Length (Inches/mm)	6.69" / 170 mm	4-2 Diameter 3.15" / 80 mm
5 Product Information			
5-1	Description	20W LED High Watt H80 Lamp Warm White / Daylight Medium Base	
5-2	Primary Application	Commercial, Industrial, Agriculture,	
5-3	Warranty	5 Years from date of purchase	
5-4	TCLP Compliant	YES	5-6 RoHS Compliant YES
5-5	Energy Star or LM79 (Y/N)	TBA	5-8 ETL TBA
6 PACKING DETAILS			
6-1	Color Box Size (cm)	1x1 8.5 X 8.5 X 18.6	6-2 Inner Carton Size (cm) N/A
6-3	Master Carton Size (cm)	1x12 36 X 27 X 20	Gross Weight ( Kg) 3.85 Net Weight ( Kg) 2.54



07/2016© Overdrive

For more information visit [www.overdrive-lighting.com.com](http://www.overdrive-lighting.com.com)



Note: This document is property of "OVERDRIVE Electronics Pvt. Ltd" and should not be copied or distributed without written permission.  
This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.